

AMAX keypad 4000 T

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Simple Icons for system condition
- ▶ Quick menu programming
- ▶ Fire, medical and panic alarms
- ▶ Zone input, on Board
- ▶ Event log on Display

The AMAX keypad 4000 T is a LCD Text keypad that is compatible with the AMAX panel 4000 / AMAX panel 4000 EN.

Up to 16 Text keypads can be connected to one AMAX 4000 panel. Text Keypads can be used as Master Keypads for different areas.

Text Keypads are Multilingual Keypads.

Functions

Arming methods

You can arm the system by entering your Code and pressing the [# / *] key, or quick arm the system by holding down the [# / *] key for 2 sec.

There are two options to arm the system:

- To arm the system and stay, press [*].
- To arm the system and leave the house, press [#].

Text keypad languages

Several languages can be displayed on the Text Keypad. The languages are based on the AMAX panel 4000 Software package.

There are three packages available:

- for AMAX panel 4000:
 - **SW Language package 1:** English, Polish
- for AMAX panel 4000 EN:
 - **SW Language package 2:** French, German, Dutch, Portuguese
 - **SW Language package 3:** English, Spanish, Swedish, Polish

- **SW Language package 3:** English, Spanish, Swedish, Polish

Fire, Medical and Panic alarms

If programmed to do so, simultaneously pressing the outside buttons of a row on any keypad triggers an audible alarm, and an alarm report is sent to the control panel. Press [4] and [6] simultaneously for a fire alarm; press [7] and [9] simultaneously for a medical alarm; and press [1] and [3] or [*STAY] and [#AWAY] simultaneously for a panic alarm.

Certifications and approvals

Region	Certification	
Germany	VdS	H113018 AMAX panel 4000 EN, IUI-AMAX4-TEXT, IUI-AMAX3-LED8, IUI-AMAX3-LED16
Europe	CE	EN 50130, EN 6100-6-3, EN 60950-1 IUI-AMAX4-TEXT, IUI-AMAX3-LED8, IUI-AMAX3-LED16
	EN5013 1	EN-ST-000137 IUI-AMAX4-Text
Belgium	INCERT	B-509-0064 IUI-AMAX4-TEXT, IUI-AMAX3-LED8, IUI-AMAX3-LED16

Parts included

Quantity	Component
1	LCD text keypad

Technical specifications

Electrical

Minimum operating voltage in VDC	10.8
Maximum operating voltage in VDC	13.8
Minimum current consumption in mA	31
Maximum current consumption in mA	100

Mechanical

Dimension in cm (H x W x D)	13.8 x 11.5 x 2.4
Weight in g	254
Color	White
Cable type	four wire, AWG18 or AWG22
Maximum cable length in m	200
Maximum cable length in m for BUS 1	700
Maximum cable length in m for BUS 2	700
Number of devices (BUS 1)	14 (8 keypads)
Number of devices (BUS 2)	14 (8 keypads)

Environmental

Minimum operating temperature in °C	-10
Maximum operating temperature in °C	55
Minimum relative humidity in %	10
Maximum relative humidity in %	95
Environmental class	II

Ordering information

AMAX keypad 4000 T

AMAX keypad 4000 T, LCD text keypad, two lines with each 18 characters

Order number **IUI-AMAX4-TEXT**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia