Acoustic signaling device, outdoor

www.boschsecurity.com







- ▶ Activation and control of the sound generator is monitored
- ▶ Wall Mounting
- ▶ Wall tamper (optional)
- ▶ Activation and control of the signaling is monitored
- ▶ Wall Mounting

The Bosch external signaling device, audio is a signaling device with an integrated sound generator for acoustic alarm.

Functions

The Bosch external signaling devices signal all alarms of the system. The connection to the security system is monitored. If it is interrupted, an alarm is triggered. The external signal devices can be mounted on walls. They can be secured optionally with a wall tamper that triggers an alarm if the device is disassembled or broken off from the wall.

Certifications and approvals

| Region | Regulatory compliance/quality marks | |
|---------|-------------------------------------|-----------------------|
| Germany | VdS | G 197023, C IUI-BES-A |
| Europe | CE | BES |

Installation/configuration notes

The sound level of the signaling device is 100 dB and has to be 10 dB above the background level. Therefore, the signaling device can be used for environments with a background level of up to 90 dB.

Parts included

| Quant ity | Component |
|--------------|-----------------------------------|
| 1 | External signaling device (audio) |
| 1 | Installation Manual |

Technical specifications

Electrical

| Au | a۱ | 0 | |
|----|----|---|--|
| | | | |

| Addio | |
|--|-----------------------------------|
| Minimum operating voltage in VDC | 10.5 |
| Maximum operating voltage in VDC | 29 |
| Rated current in mA | 300 |
| Minimum sound level at 1 m distance in dB(A) | 100 |
| Intrusion alarm tone | Complies with VdS regulation 2300 |
| Maximum alarm duration in s | 300 |

Mechanical

| Dimension in cm (H x W x D) | 22.5 x 16.5 x 11 |
|-----------------------------|----------------------|
| Weight in g | 1050 |
| Housing material | UV-resistant PVC |
| Color | Pure white, RAL 9010 |

Environmental

| Minimum operating temperature in °C | -25 |
|-------------------------------------|-----------------------------------|
| Maximum operating temperature in °C | 65 |
| Protection class | DIN 40050: IP33 DIN 40040: HUF |
| Environmental class | IV |

Ordering information

Acoustic signaling device, outdoor

For acoustic signaling of an alarm and monitored activation and control of the signaling. Order number IUI-BES-A

Represented by:

Europe, Middle East, Africa: Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com **Germany:**Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn Germany www.boschsecurity.com

North America: Bosch Security Systems, Inc. 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 onlinehelp@us.bosch.com www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia