

IP Video Surveillance

VN2008(1U)

Network Video Recorder



Overview

VIDEOTEKNIKA 2000 Series is a reliable range of Network Video Recorders with Full HD 1080p local display capability and recording benchmark of up to 5 Megapixel. The VN2008(1U) ensures unlevelled video recording quality in multiple applications on an open platform in live and also in playback. The VN2008(1U) has a standard availability of 2 Hard Disks bays allowing recording capacity of up to 12TB. Backup facility is available via the network ports through the VVMS and allows for local backups via USB.

Supported Cameras

The VN2008(1U) supports all Videoteknika IP Cameras and is fully compatible with our Videoteknika's VVMS Software. The VN2008(1U) functions on an open platform policy allowing for various 3rd party IP camera integration. Within the Videoteknika range various video encoders and video decoders are available to further more expand the flexibility for the system integrator and ensure total system synchronization. Each channel on-board the NVR allows for dual streaming with the mainstream supporting up to 5MP of record-ing resolution.

Storage Features

The VN2008(1U) allows for individual channel recording allocation ensuring the right data capacity is assigned through the relative camera depending on its streaming resolution. Instant playback is also possible via the Videoteknika reverse instant playback capability which is unique to Videoteknika NVRs. Digital zooming while live or playback is standard with any high resolution recording camera.

Supported Software

The NVR is supported by the Videoteknika VVMS-*Xpert*[™] VMS. The VVMS-*Xpert*[™] VMS is a modular Video Management Software dedicated for Videoteknika IP cameras expandable up to 1024 Channels per server. A 64 Ch version VVMS-*Advanced*[™] is supplied as a free bundled software with all Videoteknika IP Cameras. VVMS-*Mobile*[™] is also available on Iphone and Android applications. Videoteknika IP cameras are supported by various leading software development VMS partners.

Main Features

- Recording Quality up to 5MP
- 2-Way Audio
- Up to 12 Terabytes of Hard Disk space
- Self Adaptive 10m/100m/1000m network interface
- H.264 video compression
- Dual Simultaneous Streaming
- Simultaneous HDMI & VGA outputs
- HDMI & VGA (Full HD 1080p) output
- Local Data Export via USB
- Network backup export via Videoteknika VVMS software
- Multiple level users – Administrator / User 1 / User 2 (programmable)
- Privacy Masking
- Videoteknika – VVMS-*Advanced*[™] VMS software included
- Videoteknika – VVMS-*Mobile*[™] supported on App Store



IP Video Surveillance

VN2008(1U)

Network Video Recorder




Specifications

NVR Model	VN2008(1U)
Features	
IP Video Input	8-Channels
Two-way Audio	1-ch, BNC (2.0Vp-p, 1kΩ)
Recording Resolution	5MP / 3MP / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
HDMI Output	1-ch, resolution: 1920 x 1080P / 60Hz, 1920 x 1080P / 50Hz, 1600 x 1200 / 60Hz, 1280 x 1024 / 60Hz, 1280 x 720 / 60Hz, 1024 x 768 / 60Hz
VGA Output	1-ch, resolution: 1920 x 1080P / 60Hz, 1600 x 1200 / 60Hz, 1280 x 1024 / 60Hz, 1280 x 720 / 60Hz, 1024 x 768 / 60Hz
Audio Output	1-ch, BNC (Linear, 600Ω)
Playback Resolution	5MP / 3MP / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Synchronous Playback	16-Channels
SATA	2 SATA interfaces
Capacity	Each interface supports up to 6TB capacity for recording

NVR Model	VN2008(1U)
Features (Continue)	
Network Interface	1 RJ-45 10 / 100 / 1000 Mbps self-adaptive Ethernet interface
Serial Interface	1 RS-232, 1 RS-485 & 1 RS-485 keyboard
USB Interface	2, USB 2.0
Environmental	
Working Temperature	-10°C ~ +55°C
Working Humidity	10% ~ 90%
Electrical	
Power Supply	100 ~ 240 VAC, 6.3 A, 50 ~ 60 Hz
Power Consumption	≤ 13W
Physical	
Dimensions (mm)	445 (W) x 261 (D) x 44.5 (H)
Chassis	19-inch rack-mounted 1U chassis
Weight	≤ 4 Kg (13.09 lb) (without HDD or DVD-R/W)
Regulatory Certifications	FCC, CE, C-TICK, UL

Technical Diagram



Real Panel

1. Audio In
2. Audio Out
3. VGA Interface
4. HDMI Interface
5. USB Interface
6. DC12V

Real Panel (Continue)

7. Power Switch
8. LAN Network Interface



IP Video Surveillance
 VN2008(1U)
Network Video Recorder



Ordering Information

NVR Model	Network Video Recorder Details
VN2008(1U)	8-Ch, D1 to 5MP Recording Quality (Depending on Storage & Bandwith Requirements), Up to Max. 12TB of HDD space, H.264, Dual Streaming, Simultaneous HDMI & VGA outputs, Local Data Export, Network Backup

Recommended Associated Products



VVMS -Advanced™	VVMS -Xpert™	VVMS-Mobile™
Video Management Software	Video Management Software	Mobile Application
64 Channel	1024 Channel	
Mobile Application	Mobile Application	

Affiliations:



Partners:

